




**UTP**



A high-angle photograph of a golfer's feet wearing white shoes, standing on a green. A putter is positioned on the grass to the left of the feet. The scene is brightly lit, casting shadows.

**METTI A PUNTO  
UN COLPO  
VINCENTE**

A close-up shot of a white golf ball resting on a green. The ball is slightly off-center, casting a small shadow.

**POLITETRAFLUOROETILENE PTFE**





# POLITETRAFLUOROETILENE PTFE

## BARRE TONDE PIENE ESTRUSE

diametro e tolleranza in mm - peso Kg/m

Lunghezza standard: 1000 e 2000 mm

+ misure standard, normalmente pronte a magazzino

o misure a richiesta, occasionalmente pronte a magazzino

Ø	Tolleranza DIN 16980	Peso ap.	
5	0/+0,3	o	0,05
6	0/+0,4	+	0,07
7	0/+0,4	o	0,09
8	0/+0,4	+	0,12
9	0/+0,4	o	0,14
10	0/+0,4	+	0,18
12	0/+0,8	+	0,26
14	0/+0,8	+	0,36
15	0/+0,8	+	0,41
16	0/+0,8	+	0,47
18	0/+0,8	+	0,60
20	0/+0,8	+	0,73
22	0/+1,2	+	0,90
25	0/+1,2	+	1,13
27	0/+1,2	o	1,26
30	0/+1,2	+	1,65
32	0/+1,2	o	1,77
35	0/+1,2	+	2,25
38	0/+1,6	o	2,50
40	0/+1,6	+	2,90
45	0/+2,0	+	3,72

Ø	Tolleranza DIN 16980	Peso ap.	
50	0/+2,0	+	4,60
55	0/+2,4	+	5,55
60	0/+2,4	+	6,60
65	0/+2,8	+	7,75
70	0/+2,8	+	8,90
75	0/+3,2	+	10,30
80	0/+3,2	+	11,80
85	0/+3,6	+	13,20
90	0/+3,6	+	14,80
95	0/+4,0	o	16,60
100	0/+4,0	+	18,30
110	0/+5,0	+	22,00
120	0/+5,0	+	26,00
130	0/+5,0	+	30,00
140	0/+5,0	+	35,00
150	0/+6,0	+	40,00
160	0/+6,0	+	46,50
170	0/+6,0	+	53,00
180	0/+6,0	+	57,50
200	0/+6,0	+	71,00
205	0/+6,0	o	75,00

A richiesta: barre e manicotti stampati ed estrusi

## NASTRI SFOGLIATI E LASTRE

spessore tolleranza e formato in mm

+ misure standard, normalmente pronte a magazzino

o misure a richiesta, occasionalmente pronte a magazzino

Spess.	Tolleranza	Bobine H=600		Bobine H=1200		600x600 peso		1200x1200 peso		1500x1500 peso		1000x2000 peso	
		Peso appr. Kg/m		Peso appr. Kg/m		appr. kg/ lastra		appr. kg/ lastra		appr. kg/ lastra		appr. kg/ lastra	
0,3	0/+0,02	+	0,41	+	0,83								
0,5	0/+0,03	+	0,69	+	1,38								
0,8	0/+0,04	o	1,10	o	2,20								
1	0/+0,10	+	1,37	+	2,75								
1,5	0/+0,10	+	2,05	+	4,13								
2	0/+0,40*	+	2,73	+	5,50	+	1,85	+	7,30	o			
2,5	0/+0,80*	o	3,40	o	6,88	o	2,20	o	8,80				
3	0/+0,80*	o	4,09	+	8,25	+	2,50	+	10,00	o			
4	0/+0,80					+	3,50	+	13,90	o			
5	0/+0,80					+	4,50	+	18,00	+	26,95	+	23,60
6	0/+1,00					+	5,35	+	21,30	+	33,00	+	29,10
8	0/+1,20					+	7,20	+	28,80	+	43,70	+	39,60
10	0/+1,50					+	8,80	+	35,10	+	54,10	+	49,00
12	0/+15%					+	10,00	+	40,00	o	62,20	+	58,20
15	0/+15%					+	13,30	+	53,00	o	82,00	+	71,00
20	0/+15%					+	17,65	+	70,60	o	109,50	+	94,70
25	0/+15%					+	22,30	+	89,20	o	137,00	+	117,70
30	0/+15%					+	26,50	+	106,00	o	161,30	+	136,40
35	0/+15%					o	31,00	o	120,50				
40	0/+15%					+	36,10	+	141,20			o	198,50
50	0/+15%					+	42,30	+	175,00				
60	0/+15%					o	51,40	o	210,00				
70	0/+15%					o	61,00						
80	0/+15%					o	69,00						
90	0/+15%					o	78,00						
100	0/+15%					o	85,00						
130	0/+15%					o	116,00						
150	0/+15%					o	140,85						

\* Le tolleranze segnate si riferiscono alle lastre stampate. Le bobine di nastro sfogliato hanno le seguenti tolleranze: sp. 2 +0/+0,20 mm - sp 2,5 +0/+0,30 mm - sp 3 +0/+0,30 mm.

**U.T.P. S.r.l.**

Via Gran Bretagna, 1

21013 Gallarate (VA)

tel 0331 777436

fax 0331 773999

mail [info@utpsrl.com](mailto:info@utpsrl.com)

web [www.utpsrl.com](http://www.utpsrl.com)